



QM 12DC

350w Compact Passive Speaker

The QM-12DC 2-way full range loudspeaker has all the benefits of the 10DC with the added benefit of more bass and efficiency.

The 12" and 1" dual concentric driver has been optimized for vocal presence and has a very uniform frequency response. This will give higher SPL before feedback from a very compact low profile multi-purpose speaker.

The 10DC is a great versatile tool for any audio application that needs a mid powered stage monitor, wide dispersion FOH speaker, delay speaker or addition to a QM1000a system.



Power Handling:	350W
Frequency Response:	69 - 18 kHz
Max SPL@1m:	126dB
Impedance:	Ω
Connections:	2x Speakon. NL4
Midrange Woofer:	1x Quest-designed 12" Woofer
Tweeter	Driver 1" centre mounted in a "dual-concentric horn
Directivity:	Conical horn 90° x 90°
Operating Temperature Range:	-10°C - 55°C
Dimensions (WxHxD):	360x340x500
Weight:	16kg

 $^{^{\}star}$ All specifications were measured at 240VAC



^{**} Quest Engineering reserves the right to make changes in specifications, or products without prior notice.

***The figures shown above are 'real world', usable specifications and are conservative as a result. Quest Engineering does not believe in portraying misleading or exaggerated specifications.